# MANHOLE FRAMES & COVERS

**DRAIN GRATES** 

**SEWER INLETS** 



Banner Iron Works
1920 SO. KINGSHIGHWAY . ZONE 10

Saint Louis

Digitized by:



ASSOCIATION FOR PRESERVATION TECHNOLOGY, INTERNATIONAL www.apti.org

BUILDING TECHNOLOGY HERITAGE LIBRARY

https://archive.org/details/buildingtechnologyheritagelibrary

From the collection of:

NATIONAL BUILDING ARTS CENTER

http://web.nationalbuildingarts.org

# **Banner Iron Works**


1920 So. Kingshighway Blvd.

St. Louis

ZONE 10



Catalog No. 4



#### CATALOG No. 4

#### GENERAL INFORMATION

This catalog has been especially prepared for the use of Engineers and Contractors as a handy reference for selecting stock designs of iron castings for use in connection with storm and foul water sewers, streets, highways, drainage, and other work of a similar nature.

In this revised catalog, a number of new patterns that were not shown in previous issues have been added. All cuts have been made to show the necessary details only. The description of the cuts gives the general dimensions and weights.

The grouping of the various designs has been arranged so that all those of a similar nature follow in sequence. This grouping is as follows:

Round Grates	Page 4
Round Grates and Frames	Pages 5 to 8 inclusive
Round Solid Covers and Frames	Pages 9 to 22 inclusive
Round Inlet Covers	Page 23
Manhole Steps	Page 24
Rectangular Solid Covers and Frames	Pages 25 to 33 inclusive
Rectangular Grates and Frames	Pages 34 to 40 inclusive
Rectangular Grates	Pages 41 to 43 inclusive
Grate Bars and Boiler Grates	Page 44

We usually carry in stock a sufficient quantity of most patterns to meet ordinary demands. Our facilities enable us to make prompt delivery of quantity orders.

All castings are made of a high quality Gray Iron and have a tensile strength of about 25,000 p.s.i. Higher tensile strengths can be furnished if required.

We are prepared to furnish any special castings not shown. Let us quote you on your requirements.

ADDRESS ALL COMMUNICATIONS TO

#### Banner Iron Works


1920 South Kingshighway Boulevard SAINT LOUIS 10, MISSOURI

#### ROUND GRATES

To Fit in Bell Ends of Standard Clay Pipe

No. 4710





Sectional View Showing Bell End of Sewer Pipe in Concrete Floor with Grate in Place


Diameter of Pipe (Inches)	Diameter of Grate (Inches)	Weight of Grate (Pounds)
4	51/8	2
6	71/2	4
8	93/4	8
10	115/8	15
12	14	18
15	183/8	51
18	213/8	62
20	231/4	92
21	251/2	95
24	28	137
30	341/2	275
36	421/2	385

Grates for 12" pipe and under do not have center rib.

Extra Heavy grate with center rib can be furnished for 12" pipe.


#### ROUND DRAIN PLATES

To Fit in Bell Ends of Standard Clay Pipe



No. 4711

Diameter of Pipe (Inches)	Diameter of Grate (Inches)	Weight of Grate (Pounds)
4	51/8	11/4
6	7½	23/4
8	93/4	81/4



#### ROUND FRAMES WITH GRATED COVERS 10" to 321/2" Diameter

No. 4570


By using an iron frame for grate to set in, as shown here, the breaking or cracking of granitoid or clay pipe will be greatly reduced.

Frames can also be furnished with plain solid covers. NOTE: Grates may be purchased without frames if desired.

Diameter of Grate (Inches)	Outside Diameter of Frame -(Inches)	Depth of Frame (Inches)	Clear Opening (Inches)	Weight of Grate (Pounds)	Weight of Frame (Pounds)
10	14	21/2	85/8	12	21
12	16	21/2	10½	15	26
15	19	23/4	131/2	30	34
16	20	3	141/4	37	37
18	22	3	151/4	50	48
20	24	4	181/8	53	68
22	26	4	201/4	80	71
24	28	4	22	100	78
26	30	4	241/4	107	95
321/2	37	4	30	180	115

#### ROUND MANHOLE FRAME WITH 211/2" \$\phi\$ GRATED COVER


Light Duty Grate



#### No. 4791

21½"
30"
5"
191/2"
.11/4"
5 lbs.
3 lbs.


# ROUND MANHOLE FRAME WITH 213/4" \$\phi\$ GRATED COVER Heavy Duty Grate



# 4903—Grate 4791—Frame


Diameter of Grate213/4"
Diameter of Frame, outside
Height of Frame5"
Diameter of Clear Opening19½"
Depth of Rabbet11/4"
Weight of Grate
Weight of Frame

# ROUND MANHOLE FRAME WITH 26" GRATED COVER Heavy Duty Grate




#### No. 4170


Diameter of Grate26"
Diameter of Frame, outside. 36½"
Height of Frame6"
Diameter of Clear Opening24"
Depth of Rabbet
Weight of Frame250 lbs.
Weight of Grate160 lbs.



# ROUND MANHOLE FRAME WITH 26" GRATED COVER Light Duty Grate




Diameter of Grate26"
Diameter of Frame36½"
Height of Frame6"
Diameter of Clear Opening24"
Depth of Rabbet11/4"
Weight of Frame250 lbs.
Weight of Grate105 lbs.
Weight of Grate105 lbs.




# ROUND MANHOLE FRAME WITH GRATED COVER

Suitable for Heavy Traffic




#### No. 4795

Diameter of Grate235/8"
Diameter of Frame, outside37"
Height of Frame7"
Clear Opening
Depth of Rabbet
Weight of Grate147 lbs.
Weight of Frame230 lbs.




# CITY OF ST. LOUIS ROUND MANHOLE FRAME WITH GRATED COVER

Suitable for Extra Heavy Traffic




Diameter of Grate231/4"
Diameter of Frame, outside. 371/2"
Height of Frame7"
Clear Opening213/8"
Depth of Rabbet
Weight of Grate153 lbs.
Weight of Frame240 lbs.




### ROUND MANHOLE FRAME WITH SOLID COVER

Suitable for Heavy Traffic




#### No. 4796




#### CITY OF ST. LOUIS ROUND MANHOLE FRAME WITH SOLID COVER

Suitable for Extra Heavy Traffic



Diameter of Cover231/4"
Diameter of Frame, outside. 371/2"
Height of Frame7"
Clear Opening213/8"
Depth of Rabbet11/4"
Weight of Cover195 lbs.
Weight of Frame240 lbs.



#### LOCK-LID

Lock-Lid is a unique locking device for securing the covers of manhole caps to frames to eliminate rattling, reduce wear between covers and frames, and to hinder children or unauthorized persons from opening manholes.

This locking device can be adapted to most of the larger size manhole frames and covers shown in this catalog, either round or square, solid or grated covers, by a simple addition to the pattern before making the mold.

All parts are made of Gray Iron and of sturdy construction, not readily affected by corrosion, and are designed to give service comparable to the life of the cover.

Locking device consists of brackets cast integral with the cover, chamfered square removable bolts having octagon heads, and a round cammed wedge washer having a part of one side slabbed off.


The method of operation is as follows: Before placing cover in frame, the lock bolts are turned to the left as far as possible. This sets wedge washers in a position to clear frame. Cover is then placed in frame in the regular way. Lock bolts are then raised so that octagon heads clear top of cover, and are then revolved to the right until tight. This operation raises the wedge washer and clamps the cover down to the frame. The lock bolts are then dropped into the octagon recesses in the cover. This secures tight position of wedge washers in service. Operations are reversed when removing the cover.

Covers can be secured and again removed without detaching any of the locking arrangement.

Details of Locking arrangement are shown on opposite page.

#### LOCK-LID


The cuts shown on this page show the details of the locking arrangement of Lock-Lids described on opposite page as adapted to Manhole Frames and Covers No. 4796 shown on page 9. Can also be adapted to other types as explained on opposite page.




Section Thru a Frame and Cover Showing Lock in Open Position



Top View of Manhole-Cap Showing Location of Locks




Section Thru a Frame and Cover Showing Cover Locked to Frame



Bottom View of Manhole-Cap Showing Cover Locks Gripping Frame


# ROUND SUBURBAN STANDARD MANHOLE FRAME WITH SOLID COVER




#### No. 4730

Diameter of Cover233/4"
Diameter of Frame, outside36"
Height of Frame9"
Clear Opening21"
Depth of Rabbet1"
Weight of Cover85 lbs.
Weight of Frame255 lbs.

# ROUND MANHOLE FRAME WITH SOLID COVER Park Type



Diameter of Cover21½"
Diameter of Frame, outside30"
Height of Frame5"
Clear Opening19½"
Depth of Rabbet11/4"
Weight of Cover97 lbs.
Weight of Frame103 lbs.




#### CITY OF EAST ST. LOUIS, ILL., STANDARD MANHOLE FRAME WITH VENTILATED COVER

#### No. 4183

#### Solid Covers Can Also Be Furnished


Diameter of Cover2	4"
Diameter of Frame, outside3	4"
Height of Frame	7"
Clear Opening203	4"
Depth of Rabbet	4"
Weight of Cover150 lb	s.
Weight of Frame214 lb	s.




#### ROUND MANHOLE FRAME WITH SOLID COVER

Groove In Frame For Packing Flush Lift Handle On Cover


Diameter of Cover241/4"
Diameter of Frame, outside311/2"
Height of Frame9½"
Clear Opening22"
Depth of Rabbet
Weight of Cover105 lbs.
Weight of Frame177 lbs.






#### No. 4740

Diameter of Cover26	,"
Diameter of Frame, outside. 36½	"
Height of Frame6	,"
Diameter of Clear Opening24	"
Depth of Rabbet	"
Weight of Frame250 lbs	5.
Weight of Cover120 lbs	5.








#### ROUND MANHOLE FRAME WITH SOLID OUTER AND INNER COVERS


Diameter of Outer Cover26"
Diameter of Frame, outside. 361/2"
Diameter of Clear Opening 201/2"
Height of Frame8"
Depth of Rabbet
Weight of Frame355 lbs.
Weight of Outer Cover120 lbs.
Weight of Inner Cover45 lbs.

#### ROUND MANHOLE FRAME WITH SOLID COVER




#### No. 4732

Diameter of Cover233/4"
Diameter of Frame, outside34"
Height of Frame7"
Clear Opening203/4"
Depth of Rabbet11/4"
Weight of Cover85 lbs.
Weight of Frame214 lbs.



#### ROUND MANHOLE FRAME WITH 26" \$\phi\$ SOLID COVER



Diameter of Cover26"
Diameter of Frame, outside30"
Depth of Frame4"
Clear Opening24½"
Depth of Rabbet11/4"
Weight of Cover120 lbs.
Weight of Frame95 lbs.





#### CITY OF EAST ST. LOUIS, ILL., STANDARD CATCH BASIN RING AND COVER

For Concrete Caps

#### No. 4901

Diameter of Cover	. 203/4"
Thickness of Cover	3/4"
Diameter of Ring, outside	. 223/4"
Height of Ring	11/4"
Diameter of Clear Opening	.181/2"
Weight of Cover	65 lbs.
Weight of Ring	24 lbs.

#### ROUND CATCH BASIN RING AND 24" o COVER



#### No. 4902

Diameter of Cover	24"
Thickness of Cover	3/4"
Diameter of Ring, outside	. 261/4"
Height of Ring	1½"
Diameter of Clear Opening	. 221/4"
Weight of Cover	85 lbs.
Weight of Ring	39 lbs.

#### ROUND FILL CAP FRAME AND COVER



#### No. 4903

Diameter of Cover
Diameter of Frame, outside14"
Depth of Frame
Clear Opening
Depth of Rabbet
Weight of Cover
Weight of Frame


Excellent to Cover Fill Caps in Driveways of Filling Stations


#### COAL RINGS WITH SOLID COVERS

Locking Arrangement Underneath

These Coal Rings and Covers are made of heavy Metal Sections and will give many years of service when used under ordinary conditions

No. 4140





TYPE E & F COVERS ARE RIBBED UNDERNEATH


Туре	Diameter of Cover (Inches)	Diameter of Ring Outside (Inches)	Diameter of Opening (Inches)	Depth of Ring (Inches)	Depth of Rabbet (Inches)	Weight of Cover (Pounds)	Weight of Ring (Pounds)
A /	191/4	251/2	171/2	43/4	5/8	50	75
B	191/4	251/2	171/2	8	5/8	50	95
C	25	31½	24	4	5/8	95	80
D	25	31½	24	8	5/8	95	118
E	311/4	371/2	30	7	5/8	160	175
F	353/4	40	35	6	5/8	280	200

Can be furnished without locking device

## ROUND MANHOLE FRAMES WITH SOLID COVERS


No. 4761—Frame With Outer and Inner Covers Inner Cover Has Locking Device

No. 4762—Frame With Outer Cover Only
Outer Covers Can Be Furnished With Ventilating Holes When Desired



Plan showing outer cover and frame of No. 4761 and 4762


Type "A"



#### SECTION THRU No. 4761

A 3/4" diameter rubber gasket can be placed between the inner cover and the frame

**Type** "B"



SECTION THRU No. 4762

See Page 19 for Dimensions and Weights of above

#### DIMENSIONS AND WEIGHTS

#### No. 4761

	TYPE 27"	30"
Diameter of Outer Cover, Inches	33½	361/2
Diameter of Frame, outside, inches	431/2	461/2
Diameter of Clear Opening, inches	27	30
Height of Frame, inches	11	11
Weight of Frame, pounds	565	585
Weight of Outer Cover, pounds	390	455
Weight of Inner Cover, pounds	123	163
Weight of Locking Device, pounds	23	25


#### DIMENSIONS AND WEIGHTS


	ТҮРЕ "В"		
	24"	27"	30"
Diameter of Cover, inches	253/4	283/4	313/4
Diameter of Frame, outside, inches	43	46	49
Diameter of Clear Opening, inches	24	27	30
Height of Frame, inches	10	10	10
Weight of Frame, pounds	360	365	411
Weight of Cover, pounds	190	285	339

#### SQUARE MANHOLE FRAME WITH ROUND VENTILATED COVER SUITABLE FOR EXTRA HEAVY TRAFFIC


#### No. 4760

#### Solid Cover Can Also Be Furnished





Diameter of Cover	341/4"
Size of Frame, outside	42½"x42½"
Height of Frame	
Diameter of Clear Opening	315/8"
Depth of Rabbet	
Weight of Cover	400 lbs.
Weight of Frame	





# CISTERN RINGS WITH SOLID COVERS

Flush Lift Handle On Cover


No. 4150

Note—Turning of handle secures	cover to	frame
Diameter of Cover, inches	18	21
Diameter of Frame, outside, inches	27	30
Depth of Frame, inches	3	3
Diameter of Clear		
Opening, inches	171/4	193/4
Weight of Cover, pounds.	19	35
Weight of Frame, pounds	37	46









## ROUND LAMPHOLE FRAME WITH VENTILATED COVER


No. 4890

#### Solid Cover Can Also Be Furnished

Diameter of Cover	.151/4"
Diameter of Frame, outside	
Height of Frame	
Diameter of Clear Opening	.147/8"
Weight of Cover	35 lbs.
Weight of Frame	

# ROUND LAMPHOLE FRAME WITH SOLID COVER


Diameter of Cover	9"
Diameter of Frame, outside	141/4"
Height of Frame	7"
Diameter of Clear Opening	8"
Weight of Cover	. 25 lbs.
Weight of Frame	.45 lbs.



# ROUND FRAME WITH SQUARE SOLID COVER

#### No. 4840


Size of Cover
Diameter of Frame, outside38"
Size of Clear Opening . 201/2" x201/2"
Depth of Rabbet
Thickness of Cover <sup>3</sup> / <sub>4</sub> "
Height of Frame6"
Weight of Cover128 lbs.
Weight of Frame208 lbs.



#### CITY OF ST. LOUIS STANDARD STOP VALVE FRAME WITH SOLID COVER

#### No. 4882

Diameter of Cover213/4"
Size of Frame, outside 30½"x30½"
Depth of Frame61/4"
Diameter of Clear Opening20"
Depth of Rabbet
Weight of Cover101 lbs.
Weight of Frame263 lbs.



Bearing Surfaces of Frame and Cover are Machined Finish



#### CITY OF ST. LOUIS STANDARD INLET COVER

For Stone or Concrete Caps

No. 4900

Diameter of Cover	24"
Thickness of Cover	3/4"
Weight, each85	lbs.





#### ROUND INLET COVERS

For Stone or Concrete Caps

No. 4904


Diameter of Cover (Inches)	Thickness of Cover (Inches)	Weight of Cover (Pounds)
19	13⁄4	123
20	1	82






#### ROUND INLET COVER

Diameter of Cover2	23/4"
Thickness of Cover	11/4"
Weight, each146	ilbs.



#### CITY OF ST. LOUIS STANDARD CAST IRON MANHOLE STEP

No. 4922




#### CITY OF ST. LOUIS STANDARD CAST IRON TUNNEL SHAFT STEP

No. 4923

Metal 1" Thick

Weight, each......17 lbs.




#### STEEL MANHOLE STEP

No. 4920


#### SQUARE MANHOLE FRAME WITH 24"x24" SOLID COVER

Groove in Frame for Packing




#### No. 4780

Size of Cover	24"x24"
Size of Frame, outside	30"x30"
Height of Frame	4"
Size of Clear Opening	20¾"x20¾"
Weight of Cover	125 lbs.
Weight of Frame	125 lbs.



#### SQUARE MANHOLE FRAME WITH 20"x20" SOLID COVER


Groove in Frame for Packing



Size of Cover	20"x20"
Size of Frame, outside	24"x24"
Height of Frame	3"
Size of Clear Opening	17½"x17½"
Weight of Cover	50 lbs.
Weight of Frame	66 lbs.



# SQUARE METER FRAMES WITH SOLID COVERS



#### No. 4610


Style A

Style B


Size of Cover	24"x24"	30"x30"
Size of Frame, outside	29"x29"	36"x36"
Height of Frame	21/2"	3"
Size of Clear Opening22	2½"x22½"	28½"x28½"
Depth of Rabbet	3/4"	3/4"
Weight of Cover	87 lbs.	135 lbs.
Weight of Frame	82 lbs.	114 lbs.



# SQUARE CLEANOUT FRAMES WITH SOLID COVERS




Style	Size of Cover (Inches)	Size of Frame Outside (Inches)	Height of Frame (Inches)	Size of Clear Opening (Inches)	Depth of Rabbet (Inches)	Weight of Cover (Pounds)	Weight of Frame (Pounds)
A	13x13	17x17	21/2	12x12	5/8	20	29
В	16x16	20x20	21/2	15x15	5/8	32	48
C	19x19	23x23	21/2	18x18	5/8	45	48
D	371/4×371/4	40½x40½	21/2	36x36	5/8	192	101




#### RECTANGULAR MANHOLE FRAMES WITH SOLID COVERS


No. 4770



Style	Size of Cover (Inches)	Size of Frame Outside (Inches)	Height of Frame (Inches)	Size of Clear Opening (Inches)	Depth of Rabbet (Inches)	Weight of Cover (Pounds)	Weight of Frame (Pounds)
A	18x18	22x22	4	16x16	1	70	112
В	24x24	30x30	4	22x22	1	141	138
C	30x24	36x30	4	28x22	1	175	152
D	30x30	36x36	4	28x28	1	208	173




#### RECTANGULAR MANHOLE FRAMES WITH SOLID COVERS






Style	Size of Cover (Inches)	Size of Frame Outside (Inches)	Height of Frame (Inches)	Size of Clear Opening (Inches)	Depth of Rabbet (Inches)	Weight of Cover (Pounds)	Weight of Frame (Pounds)
A	18x18	21x21	21/2	153/4x153/4	1	72	50
В	24x18	27x21	21/2	22x16	1	100	66
C	30x24	33x27	21/2	28x22	1	140	75
D	36x12	39x15	21/2	34x10	1	110	61
E*	72x30	75x33	21/2	70x28	1	270	148

# SQUARE MANHOLE FRAME WITH SOLID COVER




#### No. 4600


Size of Cover	
Size of Frame, outside	29"x29"
Height of Frame	8"
Size of Clear Opening	. 21¾"x21¾"
Depth of Rabbet	11/8"
Weight of Cover	175 lbs.
Weight of Frame	260 lbs.




# SQUARE MANHOLE FRAME WITH SOLID COVER



Size of Cover	28½"x28½"
Size of Frame, outside	36"x36"
Height of Frame	9"
Size of Clear Opening	26"x26"
Depth of Rabbet	
Weight of Cover	244 lbs.
Weight of Frame	451 lbs.





#### SQUARE MANHOLE FRAME WITH SOLID COVER

No. 4883

Size of Cover38"x38"
Size of Frame, outside 44¼"x44¼"
Depth of Frame4"
Size of Clear Opening . 36½"x36½"
Depth of Rabbet"
Weight of Cover395 lbs.
Weight of Frame228 lbs.


No. 4801

Style B

Size of Outer Style A



# SQUARE MANHOLE FRAMES WITH SOLID INNER AND OUTER COVERS



Cover221	2"x22½"	$22\frac{1}{2}$ "x $22\frac{1}{2}$ "
Size of Inner		
Cover		19½"x19½"
Size of Frame,		
	1"x31"	31"x31"
Height of		
	41/2"	101/2"
Size of Clear		
	8"x18"	18"x18"
Depth of		
Rabbet	15/8"	15/8"
Weight of Out-	7.0	-/8
	40 lbs.	140 lbs.
Weight of In-		
ner Cover		70 lbs.
Weight of		
	35 lbs.	430 lbs.

Note-Style "A" not arranged for inner cover.



# RECTANGULAR FRAME WITH 14"x20" SOLID COVER

#### No. 4721

Size of Cover	14"x20"
Size of Frame, outside	18"x24"
Height of Frame	
Clear Opening	12½"x18½"
Weight of Cover	
Weight of Frame	



#### SQUARE HANDHOLE FRAME WITH 13"x13" SOLID COVER Flush Lift Handle

#### No. 4880


Size of Cover	13"x13"
Size of Frame, outside	
Depth of Frame	2"
Size of Clear Opening	$\dots 9\frac{1}{2}'' \times 9\frac{1}{2}''$
Weight of Cover	15 lbs.
Weight of Frame	15 lbs.



#### RECTANGULAR HANDHOLE FRAME WITH 7"x9" SOLID COVER

Size of Cover	7"x9"
Size of Frame, outside101/	
Depth of Frame	
Size of Clear Opening	6"x8"
Weight of Cover	4 lbs.
Weight of Frame	10 lbs.

#### SQUARE FRAME WITH 13"x13" SOLID COVER





Size of Cover	13"x13"
Size of Frame, outside	18"x18"
Height of Frame	$4\frac{1}{2}$ "
Clear Opening	12"x12"
Weight of Cover	33 lbs.
Weight of Frame	54 lbs.

# PHONE OF THE PROPERTY OF THE P


#### RECTANGULAR MANHOLE FRAME WITH 30"x24" SOLID COVER


Size of Cover	30"x24"
Size of Frame, outside	33"x27"
Depth of Frame	6"
Clear Opening	28"x22"
Weight of Cover	110 lbs.
Weight of Frame	128 lbs.

#### MANHOLE FRAME WITH BALANCED COVER

No. 4975 as shown below and No. 4985 as shown on opposite page 33, are used as the Standard Cover for Gas Main and Wire Conduit Pits, and Manholes for Water and Sewer Systems, requiring ready accessibility. They are particularly adapted for use in streets subject to heavy traffic.


The Covers are readily opened by one man by means of a key, which releases the gravity catch and then forms a handle. When open, the Cover is held in a vertical position by a counterweight which is adjusted on a shaft with lever arms. Length of shaft is made to conform to width of pit.






#### MANHOLE FRAME WITH BALANCED COVER

No. 4985 (large size)





#### CITY OF ST. LOUIS STANDARD SEWER INLET FRAME WITH GRATED COVER


Type "D" Grate

No. 4820

Size of Grate
Diameter of Frame, outside 38"
Clear Opening
Height of Frame6"
Weight of Grate156 lbs.
Weight of Frame211 lbs.

# CITY OF ST. LOUIS STANDARD SEWER INLET FRAME AND GRATED COVER WITH ADJUSTABLE CURB

# No. 4830



#### Type "A" Grate

Note — Can be furnished with full flange, as shown, or with back flange cut off.


Weight of Grate, 131 lbs.

Weight of Frame and Curb, 293 lbs.

Size of Grate	22"x16"
Diameter of Frame, outside	38"
Height of Frame	6"
Size of Curb6" wide, 8" high abo	

# RECTANGULAR SEWER INLET FRAME AND GRATED COVER WITH ADJUSTABLE CURB


#### No. 4831



Size of Grate	.24½"x12"
Size of Frame, outside	26"x18"
Height of Frame	5"
Size of Curb	e, 28" long
Clear Opening	14"x22"
Weight of Grate	56 lbs.
Weight of Frame and Curb	187 lbs.

### SEWER INLET FRAME AND GRATED COVER WITH ONE-PIECE CURB

#### No. 4841




Note — Can be furnished with full flange, as shown, or with back flange cut off.


Weight of Grate, 131 lbs.

Weight of Frame and Curb, 260 lbs.

Size of Grate22	2"x16"
Diameter of Frame, outside	38"
Height of Frame	6"
Size of Curb	" long

#### RECTANGULAR FRAMES WITH FLAT AND CONCAVE GRATES







Size of Grate
Size of Frame, outside
Height of Frame
Clear Opening
Weight of Grate

Weight of Frame....


No. 4720
14"x20"
18"x24"
23/4"
12½"x18½"
42 lbs.
62 lbs.





#### SQUARE FRAMES WITH FLAT AND CONCAVE **GRATES 13"x13"**







much	
No.	4850
13	"x13"
18	"x18"
4	11/2"
12	"x12"
2'	7 1ha

F	ווח	n'n	ñř	YOR	ñ
Ш	Ш	Ш	Ш	Ш	Ш
III	Ш		Ш		Ш
Ш	Ш	Ш	Ш	Ш	Ш
Ш	Ш	Ш	Ш	Ш	Ш

No. 4851


Fig.	
all.	
No.	4852


12/--12/

Size of Grate	13"x13"
Size of Frame, outside	18"x18"
Height of Frame	41/2"
Clear Opening	12"x12"
Weight of Grate	27 lbs.
Weight of Frame	54 lbs.


13 X13
18"x18"
41/2"
12"x12"
54 lbs.
54 lbs.

## RECTANGULAR FRAMES WITH CONCAVE GRATES










No. 4860



No. 4861

Style No.	Size of Grate (Inches)	Size of Frame Outside (Inches)	Clear Opening (Inches)	Height of Frame (Inches)	Weight of Grate (Pounds)	Weight of Frame (Pounds)
4860	14x26	23x34½	12½x24½	6	86	132
4861	14x20	21½x22	123/8x183/8	6	70	128





#### RECTANGULAR FRAME WITH GRATED 24"x36" COVER

No. 4569


Size of Grate	. 24"x36"
Size of Frame, over all	. 26"x38"
Size of Clear Opening	.21"x33"
Height of Frame	2"
Weight of Grate	252 lbs.
Weight of Frame	107 lbs.


## OVAL GUTTER INLET FRAMES WITH CONCAVE GRATES

No. 4870

STYLE "A"

Full Flange






STYLE

"B" One

Flange Cut Off






Style	Size of Grate (Inches)	Size of Frame (Inches)	Height of Frame (Inches)	Weight of Grate (Pounds)	Weight of Frame ( Pounds)
A	15x39	47x23	7	114	175
В	15x39	47x197/8	7	114	154

## SEGMENT GUTTER INLET FRAME WITH CONCAVE GRATE

No. 4871





Size of Grate...12"x31½" Size of Frame,


Size of Frame, outside.....17"x36½"

Height of Frame....23/4" Weight of Grate...50 lbs. Weight of Frame..110 lbs.

# GUTTER INLET FRAMES WITH RECTANGULAR CONCAVE GRATES

No. 4872









STYLE "B"
Back

Flange Omitted





Style	Size of Grate (Inches)	Size of Frame (Inches)	Height of Frame (Inches)	Weight of Grate (Pounds)	Weight of Frame (Pounds)
A	15x39	47x23	7	138	202
В	15x39	47x197/8	7	138	183


1-11


#### RECTANGULAR FRAME WITH GRATED COVER

For Railway Track Drains

No. 4950


#### Grate In Two Sections






Size of Double Grates, over all	9"x48"
Size of Frame, outside	20"x50"
Height of Frame	77/6"
Two Clear Openings, each	8"x231/6"
Weight of Double Grates	103 lbs.
Weight of Frame	353 lbs.

# GUTTER INLET FRAME WITH GRATED COVER (Made in two sizes)






#### No. 4862

**Style A** 15½"x24". Grate has 7 Slots 1½"x10¾".

**Style B**  $15\frac{1}{2}$ "x36". Grate has 11 Slots  $1\frac{1}{2}$ "x10 $\frac{3}{4}$ ".


	Style A	Style B
Size of Grate	. 15½"x24"	15½"x36"
Size of Frame, outside	. 24"x32"	24"x44½"
Height of Frame	. 5"	5"
Clear Opening	$14'' \times 22 \frac{1}{2}''$	14"x36½"
Weight of Grate	. 105 lbs.	172 lbs.
Weight of Frame	. 210 lbs.	256 lbs.

#### RECTANGULAR FRAME WITH 203/4"x251/2" GRATED COVER



#### No. 4865

Size of Grates.	No. of Slots
-----------------	--------------



#### SOUARE GRATES 1" THICK

No. 4571

Size of Grate (Inches)	Thickness of Grate (Inches)	Weight Each (Pounds)
8x 8	1	9
10x10	1	14
12x12	1	20
20x20	1	53

#### RECTANGULAR GRATE 14"x21"



No. 4572				
Size of Grate		14"x21"		
Thickness	11037	1"		

Can Also Be Furnished in 11/2" and 2" Thickness

#### CITY OF EAST ST. LOUIS, ILL., STANDARD INLET GRATE 18"x24"







NO. 4003
Size18"x24"
Thickness of Metal
Depth of Rib, over all3"
Weight120 lbs.

#### RECTANGULAR INLET GRATE No. 4864

Used in Parks and Cemeteries when leaves are a problem



Size of Grate14"x22"
Thickness of Grate
No. of Slots




# RECTANGULAR DRAIN GRATES

No. 4574

Size of Grate (Inches)	Thickness (Inches)	No. of Slots	Weight Pounds
17x21	2	8	102
17x41	2	16	185
17x46	2	18	211

Excellent to take storm water at foot of sloping drive leading to garage or similar opening.

# RECTANGULAR DRAIN GRATE No. 4575



Size of Grate	
Thickness of Grate	1" at edges, 13/8" at center
No. of Slots	
Size of Slots	1.03"x12"
Weight of Grate	155 lbs.


# RECTANGULAR DRAIN GRATE No. 4576



Size of Grate20"x26"
Thickness of Grate
No. of Slots24
Size of Slots <sup>3</sup> / <sub>8</sub> "x17"
Weight of Grate124 lbs.

#### CITY OF ST. LOUIS STANDARD GRATE

No. 4848 (Type A)



Size of Grate 15"x30"

Thickness of Grate 2½"


26 Slots 1½"x5½"

Weight of Grate 184 lbs.

Welded steel Angle Frames can be furnished for this grate. Details on request.

#### CITY OF ST. LOUIS STANDARD GRATE

No. 4849 (Type B)




Size of Grate 15"x27½"

Thickness of Grate

21/2"

20 Slots 1½"x5½"

Weight of Grate 163 lbs.



#### HIGHWAY GRATE

No. 4820 (Type D)

Size of Grate	22"x22"
Thickness of Grate	21/4"
No. of Openings	49
Size of Openings	2"x2"
Weight of Grate	156 lbs.


Additional rows of 2" \( \simeg \) holes can be added to either length or width or both, when extra large grates are required.

# CAST IRON GRATE BARS No. 5000



All Bars are Double, 3 inches wide, 3/4-inch metal, 3/4-inch air space Bars under 4' 0" long have one separator in center

Length	Depth in Center (Inches)	Weight Each (Pounds)	Length	Depth in Center (Inches)	Weight Each (Pounds)
2'6"	21/2	28	4' 3"	33/4	60
3'0"	23/4	30	4' 6"	4	65
3' 3"	23/4	31	5′0"	41/4	76
3' 6"	3	36	5' 6"	41/2	82
3'9"	31/4	42	6'0"	5	94
4'0"	31/2	54	6' 6"	5	121



# ROUND CAST IRON GRATES FOR BOILERS

No. 5001

Diameter (Inches)	No. of Sections	Weight Each (Pounds)	Diameter (Inches)	No. of Sections	Weight Each (Pounds)
24	3	98	36	4	253
25	3	99	37	4	255
26	3	120	38	4	310
27	3	122	39	4	315
28	3	160	40	4	339
29	3	163	41	4	342
30	3	190	42	4	400
31	3	194	43	4	402
32	3	201	44	4	441
33	3	205	45	4	445
34	4	225	46	4	465
35	4	231	47	4	490

In this Catalog we have shown Standard designs for which we have patterns. If you do not find a size which can be adapted to your conditions, send us a sketch or drawing and we will be glad to quote on your special needs. We operate a well-equipped pattern shop, as well as a machine shop in connection with our Gray Iron Foundry so are well prepared to handle all of your Foundry requirements.

We are also fabricators of Structural Steel and Miscellaneous Iron Work for buildings and industries, and carry in stock I Beams, Channels, Angles, Bars and Plates. When you are in the market for this class of material we solicit your inquiries.

#### INDEX

Patter	n No. DESCRIPTION	Page
4140	Coal Rings with Solid Covers, 17½", 24", 30", 35" diameter	. 17
4150	Cistern Rings with Solid Covers, 18", 21" diameter	
4170	Round Manhole Frame with 26" diameter Grated Cover, heavy duty	. 7
4171	Round Manhole Frame with 26" diameter Grated Cover, light duty	./ 7
4183	City of E. St. Louis, Ill., Standard Manhole Frame with Ventilated Cover, 24" diameter	. 13
4569	Rectangular Frame with Grated 24" x 36" Cover	. 37
4570	Round Frames with Grated Covers, 10" to 32½" diameter.	
4571	Square Grates 1" thick, 8" x 8", 10" x 10", 12" x 12", 20" x 26"	
4572	Rectangular Grate, 14" x 21"	. 41
4574	Rectangular Drain Grates, 17" x 21", 17" x 41", 17" x 46"	
4575	Rectangular Grate, 14" x 60"	
4576	Rectangular Drain Grate, 20" x 26"	
4600	Square Manhole Frame with Solid Cover, 24" x 24"	
4610	Square Meter Frame with Solid Covers, 24" x 24", 30" x 30"	
4620	Square Cleanout Frames with Solid Covers, 13" x 13", 16" x 16", 19" x 19",	26
4710	$37\frac{1}{4}$ " x $37\frac{1}{4}$ "	. 26
4711	Round Drain Plates 51/8" to 93/4", to fit in Bell Ends of Standard Clay Pipe.	
4720	Rectangular Frame with flat grate, 14" x 20"	
4721	Rectangular Frame with 14" x 20" Solid Cover	
4730	Round Suburban Standard Manhole Frame with Solid Cover 23¾" diameter	
4731	Round Manhole Frame with Solid Cover 24¼" diameter	
4732	Round Manhole Frame with Solid Cover 23¾" diameter	
4733	Round Manhole Frame with Solid Cover 26" diameter, diameter of frame, outside 30"	
4740	Round Manhole Frame with Solid Cover 26" diameter, diameter of frame, outside 36½"	
4750	Square Manhole Frame with Solid Cover, 28½" x 28½"	. 28
4760	Square Manhole Frame with Round Ventilated Cover, 341/4" diameter	. 20
4761	Round Manhole Frames with Inner and Outer Solid Covers, 33½" and 36½" diameters	18–19
4762	Round Manhole Frames with Solid Outer Cover only, 25¾", 28¾", 31¾" diameters	. 18–19
4770	Rectangular Manhole Frames with Solid Covers, 18" x 18", 24" x 24", 30" x 24", 30" x 30"	27
4771	Rectangular Manhole Frames with Solid Covers, 18" x 18", 24" x 18", 30" x 24", 36" x 12", 72" x 30"	27
4772	Rectangular Manhole Frame with 30" x 24" Solid Cover	31
4780	Square Manhole Frame with 24" x 24" Solid Cover	
4781 4790	Square Manhole Frame with 20" x 20" Solid Cover	
4790	Round Manhole Frame with Solid Cover, 21½" diameter	12
4791	Round Manhole Frame with Grated Cover, 21½ diameter, light duty	. 6
4795	Round Manhole Frame with Grated Cover, 21% diameter, neavy duty	. 0
1173	heavy traffic	8
4796	Round Manhole Frame with Solid Cover, 235/8" diameter, suitable for heavy traffic	
4798	City of St. Louis Round Manhole Frame with Grated Cover, 231/4" diameter, suitable for extra heavy traffic.	

### INDEX—Continued

	rn No. DESCRIPTION	Page
4799	City of St. Louis Round Manhole Frame with Solid Cover, 23¼" diameter, suitable for extra heavy traffic	. 9
4800	Round Manhole Frame with Solid Outer and Inner Covers, 26" diameter	. 14
4801	Square Manhole Frames with Solid Inner and Cuter Covers, 221/2" x	. 29
4820	City of St. Louis Standard Sewer Inlet Frame with Grated Cover, 22" x 22".	. 34
4820	Highway Grate, 22" x 22"	43
4830	City of St. Louis Standard Sewer Inlet Frame and Grated Cover with ad-	
	justable curb, 22" x 16", with curb, type "A" grate	. 34
4831	Rectangular Sewer Inlet Frame and Grated Cover with adjustable curb, $24\frac{1}{2}$ " x 12", with curb	35
4840	Round Frame with Square Solid Cover, 22" x 22"	. 22
4841	Sewer Inlet Frame and Grated Cover with one-piece curb, 22" x 16"	. 35
4848	City of St. Louis Standard Grate, 15" x 30"	. 43
4849	City of St. Louis Standard Grate, 15" x 27½"	. 43
4850	Square Frame with Flat Grate, 13" x 13"	. 43
4851	Square Frame with Concave Grate, 13" x 13"	. 36
4852	Square Frame with Concave Grate, 13 x 13	. 36
4853	Square Frame with Concave Grate, 13" x 13", (heavy)	. 36
4854	Square Frame with Solid Cover, 13" x 13"	. 31
4855	Rectangular Frame with Concave Grate, 14" x 18", (grating 14" way)	. 36
4860	Rectangular Frame with Concave Grate, 14" x 18", (grating 18" way)	. 36
	Rectangular Frame with Concave Grate, 14" x 26"	. 37
4861	Rectangular Frame with Concave Grate, 14" x 20".	. 37
	Gutter Inlet Frame with Grated Cover, 15½" x 24", 15½" x 36"	. 40
4863	City of E. St. Louis, Ill., Standard Inlet Grate, 18" x 24"	. 41
4865	Rectangular Inlet Grate, 14" x 22"	. 41
4870	Rectangular Frame with Grated Cover, 2034" x 25½"	. 40
	Oval Gutter Inlet Frames with Concave Grates, 15" x 39"	. 38
4871	Segment Gutter Inlet Frame with Concave Grate, 12" x 31½"	. 38
4880	Gutter Inlet Frame with Rectangular Concave Grates, 15" x 39"	. 39
4881	Rectangular Handhole Frame with Solid Cover, 7" x 9"	. 30
4882	City of St. Louis Standard Stop Valve Frame with Solid Cover, 213/4"	
4883	Square Manhole Frame with Solid Cover, 38" x 38"	29
4890	Round Lamphole Frame with Ventilated Cover, 151/4" diameter, solid cover available	21
4891	Round Lamphole Frame with Solid Cover, 9" diameter	21
4900	City of St. Louis Standard Inlet Cover, 24" diameter	23
4901	City of E. St. Louis, Ill., Standard Catch Basin Ring and Cover, 203/4" diameter	16
4902	Round Catch Basin Ring and Cover, 24" diameter	16
4903	Round Fill Cap Frame and Cover, 10" diameter	16
4904	Round Inlet Covers, 19" and 20" diameters	23
4905	Round Inlet Cover, 22¾" diameter	23
4920 /	Steel Manhole Step	24
4922	City of St. Louis Standard Cast Iron Manhole Step.	24
4923	City of St. Louis Standard Cast Iron Tunnel Shaft Step	
4975	Manhole Frame with Balanced Cover, 21½" x 31½" (small size)	32
4985	Manhole Frame with Balanced Cover, 2734" x 3414" (large size)	33
5000	Cast Iron Grate Bars, 2' 6" to 6' 6"	44
5001	Round Cast Iron Grates for Boilers, 24" to 47" diameter	44
	Lock-Lid (for securing the Covers of Manhole-Caps to Frames)	0-11

### OTHER PRODUCTS

### **Industrial Castings**

- (A) GRAY IRON
- (B) HIGH TENSILE STRENGTH
- (C) WEAR AND ABRASION RESISTING
- (D) HEAT RESISTING
- (E) PRESSURE TIGHT

We also carry in stock a quantity of billets for immediate shipment in sizes from  $\frac{3}{4}$ "  $\phi$  to 8"  $\phi$  in 13" lengths. These billets have a tensile strength of 40,000 lbs. p.s.i. minimum.

Phone or write

### BANNER IRON WORKS

1920 S. Kingshighway Blvd. ST. LOUIS 10, MO.

